



1700 North Broadway • Suite 128
Rochester, MN 55906
507-282-8206 • FAX 281-0391

THE FOLLOWING ITEMS ARE CONDITIONS FOR PERMIT ISSUANCE FOR REROOFING

STRICT COMPLIANCE IS MANDATORY

1. Only two (2) layers of roof covering are permitted. R907.3
2. Ice barrier is required under first layer. R907.3
3. **Provide ice dam protection on all roof edges. Protection shall extend from the eave's edge to a point at least 24" inside the exterior wall line. R905.2.7.1 Exception: Detached accessory structures that contain no conditioned floor area.**
4. Attic ventilation (house) to be provided that equals one (1) square foot of ventilation for each 150 square feet of attic space. 1/300 is allowed if half of the ventilation opening is in the top 1/2 of the roof. R806.1-R806.3
5. Sidewall Flashing: Flashing against a vertical sidewall shall be by the step-flashing method. R905.2.8.4
6. Existing buildings and structures: Kick-out flashings shall be required in accordance with Section R903.2.1 when simultaneously re-siding **and** reroofing existing buildings and structures. R903.2.1.1
7. Asphalt shingles shall be fastened to solidly sheathed decks, or one inch (1") thick nominal wood boards. R905.2.1
8. This structure must comply with all portions of the Minnesota State Building Code whether noted on this plan or omitted. Failure to note any detail(s) on the plan does not remove the builder from the responsibility of complying with the Building Code.

Jay Kruger
Building Official

CALL CMS FOR FINAL INSPECTION